

## LOADER/BACKHOE OPERATOR TEST

1. The operator of the loader/backhoe is to inspect the machine
  - a. once a month.
  - b. at the beginning of each shift.
  - c. once a week.
2. It is not necessary to have all of the controls labeled.
  - a. True
  - b. False
3. All warning decals on the machine must be legible.
  - a. True
  - b. False
4. Hydraulic fluid leaks are not a big concern on loader/backhoes.
  - a. True
  - b. False
5. The operator's manual needs to be located
  - a. in the company office.
  - b. on the machine.
  - c. at the maintenance shop.
6. The operator of the loader/backhoe is responsible for reading the operator's manual.
  - a. True
  - b. False
7. When the backhoe of the loader/backhoe is raised and extended, the machine's stability
  - a. increases.
  - b. decreases.
  - c. doesn't change.
8. When the loader/backhoe is crossing a slope, the machine is more susceptible to a rollover.
  - a. True
  - b. False
9. To improve the stability of the loader/backhoe when crossing a slope, the backhoe can be swung
  - a. uphill.
  - b. down hill.
  - c. straight back.

ARXCIS, INC.  
Kingston, WA

18. Seat belts must be worn
  - a. only when traveling the machine.
  - b. on steep slopes.
  - c. at all times.
  
19. When climbing off of the loader/backhoe, the operator should:
  - a. face the machine.
  - b. jump from the machine.
  - c. climb over the back of the backhoe.
  
20. Who is responsible for job site safety?
  - a. Job site foreman
  - b. Everyone
  - c. Company safety officer
  
21. The danger area when the backhoe is in operation is considered everywhere the backhoe can reach.
  - a. True
  - b. False
  
22. Before a worker enters the danger area of a backhoe, he should
  - a. make sure he can get in and out without being hit by the backhoe.
  - b. establish eye contact with the operator.
  - c. yell before entering the danger area.
  
23. When a loader/backhoe is in operation, workers should not stand in the bucket or stabilizer pads.
  - a. True
  - b. False
  
24. When working around a loader/backhoe, the worker should always face the machine.
  - a. True
  - b. False
  
25. Before excavating with a loader/backhoe, all underground hazards should be located.
  - a. True
  - b. False
  
26. When setting up the loader/backhoe, the stabilizer pads should be placed at the edge of the excavation.
  - a. True
  - b. False

ARXCIS, INC.  
Kingston, WA

36. Proper barricades are required at all job sites involving excavations.
- True
  - False
37. Where should the operator's manual for special attachments need to be located.
- On the machine
  - In the company office
  - Is not required
38. The boom transport lock device has to be engaged before loading the machine on a transport trailer.
- True
  - False
39. A transport vehicle wheels are not required to be blocked when loading a loader/backhoe.
- True
  - False
40. Tie-down chains are not required for securing the loader/backhoe to a transport vehicle.
- True
  - False